

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-241586

(43)Date of publication of application : 28. 08. 1992

(51)Int. Cl.

H04N 5/335

(21)Application number : 03-014788 (71)Applicant : SONY CORP

(22)Date of filing : 14. 01. 1991 (72)Inventor : OGISHI TAKESHI

(54) SOLID-STATE IMAGE PICKUP DEVICE

(57)Abstract:

PURPOSE: To easily suppress fixed pattern noise caused by the dispersion of a threshold voltage or the like at low cost by easily obtaining an offset corrected image signal without using an external memory or the like at an AMI.

CONSTITUTION: At each picture element 1, a column select signal having a binary amplitude is supplied to a column select line Lx to which a horizontal switching transistor Tx and a transistor Trs for reset are connected, and a signal current superimposing a real signal current and an offset current to and an offset current are successively outputted to a signal line Ls. Then, the respective signal current and offset current are converted to voltages by an operational amplifier 4 and defined as a signal output voltage and a reset output voltage respectively and afterwards, these output voltages Vo are sampled/held, for example, so as to subtract the above-mentioned signal output voltage and reset output voltage by using a differential amplifier, for example, in the rear step.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's
decision of rejection]

[Kind of final disposal of
application other than the

examiner's decision of rejection or
application converted registration]

[Date of final disposal for
application]

[Patent number]

[Date of registration]

[Number of appeal against
examiner's decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]